



Drainlocks are produced in dimensions 1" to 12".

The Drainlocks made by TEE AS are made up of corrosion resistant materials. Glasfiber reinforced polymide (PA6), non corrosive 316L, and oil resistant, and will therefor have a long useful life.

May we also point out that the expansion plugs are not designed to be used as Blanking plugs during pressure testing. Please contact us if special versions would be of interest. We design and manufacture to the customes spesifications.

Dimension	Expansion	Weight(kgs)
1.5"	35-50 mm.	0.2
2"	50-65 mm.	0.25
2.5"	65-75 mm.	0.4
3"	70-90 mm.	0.45
3.5"	90-105 mm.	0.55
4"	95-118 mm.	0.6
4.5"	110-125 mm.	0.65
5"	120-140 mm.	0.8
5.5"	130-150 mm.	1.4
6"	145-175 mm.	1.10
7"	175-200 mm.	2.18
8"	200-230mm.	1.75
9"	225-255mm.	4.0
10"	245-275 mm.	4.5
12"	300-330 mm.	8.0

Features and Benefits

The Plugs are used in connection with: Maintenance work and also tightening of deck drains and pipes.

During operations where the pipe plugs shall withstand lower differential pressure and the safety has priorety, this is our recomend stopper.

Characteristics of this product are:

- Stabile when stocked onboard
- Non-corrosive
- High quality

